


"REPLACEMENT SHEET"

Fig. 3

Residual polymers unstripped



20

25


30

35

"REPLACEMENT SHEET"

Fig. 4

After stripping with 100 ppm of H_2SiF_6



20

25


30

35

"REPLACEMENT SHEET"

Fig. 5

After stripping with 500 ppm of H_2SiF_6



20

25


30

35

"REPLACEMENT SHEET"

Fig. 6

After stripping with 1000 ppm of H_2SiF_6



20

25


30

35

"REPLACEMENT SHEET"

Fig. 7


After stripping with 100 ppm of HF



"REPLACEMENT SHEET"

Fig. 8

After stripping with 200 ppm of HF



20

25

30

35

"REPLACEMENT SHEET"


Fig. 9

After stripping with 500 ppm of HF

5

10

15



20

25

30


35

"REPLACEMENT SHEET"

Stripping results in a Mattson AWP tank processor with various H_2SiF_6 concentrations.

Fig. 10

After stripping with 100 ppm of H_2SiF_6



"REPLACEMENT SHEET"


Fig. 11

After stripping with 600 ppm of H_2SiF_6

5

10

15



20


25

30

35

"REPLACEMENT SHEET"

5 **Fig. 12:** Result after use of a composition with added surfactant.



25

30

35

"REPLACEMENT SHEET"

Fig. 13

Comparison with Fig. 12: Result after use of a composition without added surfactant.

